



General Product Specifications

Eureka Pearl Inbuilt & Jindara Tilga Inbuilt

Dimensions and Specifications		
	Masonry Insert	Zero Clearance Insert
Overall Dimension (Height)	640 mm	674 mm
Overall Dimension (Width)	855 mm	850 mm
Fascia Depth	16 mm	3 mm
Rear Casing Dimension (Height)	595 mm	N/A - See Zero Clear-
Rear Casing Dimension (Width)	751 mm	N/A - See Zero Clear-
Rear Casing Dimension (Depth)	484 mm	N/A - See Zero Clear-
Firebox Dimension (Height)	362 mm	
Firebox Dimension (Width)	522 mm	
Firebox Dimension (Depth)	432 mm	
Door Opening Dimension (Height x Width)	256 x 522mm	
Glass Viewing Size (Height x Width)	285 x 570mm	
Flue Size	150mm	
Back of Fascia to Flue Centre	326 mm	N/A - See Zero Clearance Install Guide
Shipping weight	162kg	256kg
Linings	Cast Iron Liners on walls	
Baffle thickness	8mm	
Glass Type	Flat, toughened 5mm ceramic	
Hearth & Clearance Requirements		
Min. Hearth Width	945 mm	
Min. Hearth Depth (in front of unit)	550 mm	
Min. Hearth Thickness	18 mm	
Clearance to Mantle Upright	55 mm	
Clearance to Mantel Shelf (from appliance base)	1500mm*	
Clearance to Mantel Breast Plate (from appliance base)	1410 mm	
	* denotes mantle deflector required (included in wood heater)	
Emissions and Efficiency		
Emissions	1.0g/kg	
Efficiency	74%*	
Peak Output	12kw	
	*Peak efficiency % quoted	
CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION		