



General Product

Specifications

Eureka Ruby Mk2 Modular &

Jindara Grange Mk2 Modular

| Dimensions and Specifications | |
|---|---|
| Overall Dimension (Height) | 676 mm |
| Overall Dimension (Width) | 748 mm |
| Overall Dimension (Depth) | 548 mm |
| Firebox Dimension (Height) | 408 mm |
| Firebox Dimension (Width) | 580 mm |
| Firebox Dimension (Depth) | 431 mm |
| Door Opening Dimension (Height x Width) | 275 x 580mm |
| Glass Viewing Size (Height x Width) | 310 x 630mm |
| Back of Heater to Flue Centre | 205 mm |
| Flue Size | 150mm |
| Shipping weight | 212kg |
| Linings | Cast Iron Liners on walls |
| Baffle thickness | 8mm |
| Glass Type | Flat, toughened 5mm ceramic |
| Hearth & Clearance requirements - He | eater only, perforated outer flue kit |
| Min. Hearth Width | 1000 mm |
| Min. Hearth Depth | 898 mm |
| Min. Hearth Thickness | 140 mm |
| Min. In Front Of Unit | 330 mm |
| Rear Clearance | 50mm* |
| Side Clearance | 325 mm |
| Corner Clearance | 50mm* |
| | * denotes standard flue shield required (included |
| | in wood heater) |
| Hearth & Clearance requirements | |
| Min. Hearth Width | 1000 mm |
| Min. Hearth Depth | 898 mm |
| Min. Hearth Thickness | 140 mm |
| Min. In Front Of Unit | 330 mm |
| Rear Clearance | 50mm* |
| Side Clearance | 325 mm |
| Corner Clearance | 50mm* |
| | * denotes standard flue shield required (included |



Woodheating

General Product

Specifications

Eureka Ruby Mk2 Modular &

Jindara Grange Mk2 Modular

| | ments - With optional bench, perforated outer flue kit |
|---|---|
| Min. Hearth Width | 1000 mm |
| Min. Hearth Depth | 900 mm |
| Min. Hearth Thickness | 9 mm |
| Min. In Front Of Unit | 300mm |
| Rear Clearance | 50mm* |
| Side Clearance | 325 mm |
| Corner Clearance Hearth & Clearance regu | 50mm* * denotes standard flue shield required (included in wood heater) irements - With optional bench, solid outer flue kit |
| | |
| Min. Hearth Width | 1000 mm |
| Min. Hearth Depth | 900 mm |
| Min. Hearth Thickness | 9 mm |
| Min. In Front Of Unit | 300mm |
| Rear Clearance | 50mm* |
| Side Clearance | 325 mm |
| Corner Clearance | 50mm* * denotes standard flue shield required (included in wood heater) |
| | Bench Dimensions |
| Height | 280 mm |
| Width | 1200 mm |
| Depth | 550 mm |
| Between Legs | 1080 mm |
| | Emissions and Efficiency |
| Emissions | 1.3k/kg |
| Efficiency | 76%* |
| Peak Output | 17kw |
| | *Peak efficiency % quotec |
| | OVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION |